

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. **(original)** A method for measuring the wear of a disk of composite ceramic material of a disk brake comprising the following operations:

- measuring the temperature (T) of the disk at a predetermined frequency (f),
 - at every temperature measurement, calculating a wear increment (Δi) as a function of the measured temperature (T),
 - summing the calculated wear increments (Δi),
 - comparing the sum of the wear increments with the predetermined limiting wear index (i_{lim}) and
 - signalling the eventual overstepping of the limiting wear index (i_{lim}).

2. **(original)** A method in according with Claim 1, wherein the operation of calculating a wear increment (Δi) comprises the following steps:

- comparing the measured temperature (T) with a predetermined reference temperature (T_r) and
- calculating the wear increment (Δi) by using a first and a second predetermined function of the temperature when the comparison shows that the measured temperature (T), respectively, does and does not exceed the predetermined reference temperature (T_r).

3. **(original)** A method in accordance with Claim 2, wherein both the first and the second predetermined function are exponential functions of the temperature.

4. **(original)** A method in accordance with Claim 3, wherein the first and the second predetermined function are the type:

$$\Delta i = \alpha * 1/f * \exp(\beta * T/T_0)$$

Where Δi is the wear increment, T is the measured temperature, T_0 is a predetermined temperature constant, α is a first predetermined constant coefficient, β is a second predetermined constant coefficient, and f is the sampling frequency.

5. **(original)** A method in accordance with Claim 4, wherein the predetermined frequency (f) is a frequency chosen within the range comprised between 5 and 50 Hz, the predetermined reference temperature (T_r) is a temperature chosen within the range comprised between 350°C and 550°C, the predetermined temperature constant (T_0) is a temperature chosen within the range comprised between 350°C and 550°C and in which the constant coefficient α of the first function is comprised between 0 and 0.1 and the constant coefficient β of the first function is comprised between 0 and 4, while in the second function the constant coefficient α is comprised between 0 and 0.01 and the constant coefficient β is comprised between 0 and 15.

6. **(currently amended)** A method in accordance with Claim 1 ~~any one of the preceding claims~~, wherein the limiting wear index (i_{lim}) is experimentally obtained.

7. **(currently amended)** A system for measuring the wear of a disk of composite ceramic material of a disk brake comprising:

- a sensor ~~(25)~~ for detecting the temperature of the disk,
- means ~~(26)~~ for sampling the temperature detected by the sensor at a predetermined frequency (f),
- processing means ~~(28)~~ capable of calculating a wear increment (Δi) for every sampled temperature and summing the calculated wear increments,
- means ~~(29)~~ for memorizing the sum of the wear increments,
- means ~~(28)~~ for comparing the memorized sum with a predetermined limiting wear index (i_{lim}) and
- signalling means ~~(31)~~ for signaling whether the comparison shows that the predetermined limiting wear index (i_{lim}) has been exceeded.

8. **(currently amended)** A system in accordance with Claim 7, wherein the sensor ~~(25)~~ comprises a thermocouple mounted inside a support ~~(34)~~ made of material that is a good conductor of heat fixed to a brake pad ~~(35)~~ of the disk brake.

9. **(currently amended)** A system in accordance with Claim 8, wherein the support ~~(34)~~ of the thermocouple has a terminal appendix of low thermal inertia of which the end just projects beyond the surface of the brake pad ~~(35)~~ that comes into contact with the disk.

10. **(currently amended)** A system in accordance with Claim 9, wherein the thermocouple is housed in a blind hole of the support ~~(34)~~ adjacent to the internal end of the terminal appendix.

11. **(currently amended)** A system in accordance with Claim 8 ~~any one of Claims 8 to 10~~, wherein at least one lead of the thermocouple is inserted in a sheath fixed to the supporting plate of the brake pad ~~(35)~~ that forms a projecting element ~~(36)~~ facing the disk of the disk brake, said projecting element ~~(36)~~ being in a position such that the sheath and the lead may be consumed by friction with the disk when the brake pad ~~(35)~~ has become thinned down to a predetermined limiting thickness.